

NB SERIES NICKEL PLATED BRASS 450 PSI WOG MINI BALL VALVES

ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE



NB & NB-M SERIES

- 29"Hg - 450 PSIG WOG, Cold Non-Shock
- Blowout-Proof Stem
- PTFE Seats
- Chrome Plated Brass Ball
- Second O-Ring Stem Seal
- Temperature: -20°F to 200°F

NPT SIZE	PART # Female/female	PART # Male/Female
1/8"	NB-1	NB-M1
1/4"	NB-2	NB-M2
3/8"	NB-3	NB-M3
1/2"	NB-4	NB-M4
3/4"	NB-6	NB-M6



B2 SERIES BRASS 1500 PSI WOG PANEL MOUNT BALL VALVES

B2 SERIES

- Brass 2-Way Ball Valve
- 29"Hg - 1500 PSIG WOG, Cold Non-Shock
- Blowout-Proof Stem
- Teflon® Ball Seats
- Nickel Plated Brass Ball
- Double O-Ring Stem Seals (Primary Viton; Secondary-Aflas)
- Temperature: 10°F to 350°F

NPT SIZE	PART #
1/8"	B2-F1
1/4"	B2-F2
3/8"	B2-F3
1/2"	B2-F4



B290 SERIES BRASS 1500 PSI WOG 90° PANEL MOUNT BALL VALVES

B290 SERIES

- Brass 2-Way Ball Valve
- 29"Hg - 1500 PSIG WOG, Cold Non-Shock
- Blowout-Proof Stem
- Teflon® Ball Seats
- Nickel Plated Brass Ball
- Double O-Ring Stem Seals (Primary Viton; Secondary-Aflas)
- Temperature: 10°F to 350°F

NPT SIZE	PART #
1/8"	B290-F1
1/4"	B290-F2
3/8"	B290-F3
1/2"	B290-F4



B3 SERIES BRASS 1500 PSI WOG 3-WAY PANEL MOUNT BALL VALVES

B3 SERIES

- Brass 3-Way Ball Valve
- L-Port 180° Rotation
- 29"Hg - 1500 PSIG WOG, Cold Non-Shock
- Blowout-Proof Stem
- Teflon® Ball Seats
- Nickel Plated Brass Ball
- Double O-Ring Stem Seals (Primary Viton; Secondary-Aflas)
- Temperature: 10°F to 350°F

NPT SIZE	PART #
1/8"	B3-F1
1/4"	B3-F2
3/8"	B3-F3
1/2"	B3-F4

