

SGF SERIES STAINLESS 2-WAY FULL PORT 1000 PSI BALL VALVES

ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE



~ Available Only with Locking Device ~

SGF SERIES

- Stainless Steel, Full Port
- 29"Hg - 1000 PSIG WOG, Cold Non-Shock
- CF8M Body, 316 Stainless Steel Ball and Stem
- Blowout Proof Stem
- RTFE Seats
- Temperature -20°F to 450°F

NPT SIZE	PART #
1/4"	SGF-2
3/8"	SGF-3
1/2"	SGF-4
3/4"	SGF-6
1"	SGF-8
1-1/4"	SGF-10
1-1/2"	SGF-12
2"	SGF-16
2-1/2"	SGF-20
3"	SGF-24
4"	SGF-32



S2S SERIES STAINLESS 2-WAY STD. PORT 2000 PSI BALL VALVES

~ Available Only with Locking Device ~

S2S SERIES

- Stainless Steel, Standard Port
- 29"Hg - 2000 PSIG WOG, Cold Non-Shock (1/4"-1") (1500 PSI 1-1/4"-2")
- CF8M Body, 316 Stainless Steel Ball and Stem
- Blowout Proof Stem
- RTFE Seats
- Temperature -20°F to 450°F

NPT SIZE	PART #
1/4"	S2S-2
3/8"	S2S-3
1/2"	S2S-4
3/4"	S2S-6
1"	S2S-8
1-1/4"	S2S-10
1-1/2"	S2S-12
2"	S2S-16



S3F SERIES STAINLESS 3-PIECE 2-WAY 1000 PSI NPT BALL VALVES

~ Available Only with Locking Device ~

S3F SERIES

- Stainless Steel, Full Port
- 29"Hg - 1000 PSIG WOG, Cold Non-Shock (1/4"-2") (800 PSI 2-1/2"-3")
- CF8M Body, 316 Stainless Steel Ball and Stem
- RTFE Seats
- Temperature -20°F to 450°F

NPT SIZE	PART #
1/4"	S3F-2
3/8"	S3F-3
1/2"	S3F-4
3/4"	S3F-6
1"	S3F-8
1-1/4"	S3F-10
1-1/2"	S3F-12
2"	S3F-16
2-1/2"	S3F-20
3"	S3F-24



S3F-W SERIES STAINLESS 3-PIECE 2-WAY 1000 PSI SOCKET WELD

~ Available Only with Locking Device ~

S3F SERIES

- Stainless Steel, Full Port
- 29"Hg - 1000 PSIG WOG, Cold Non-Shock (1/4"-2") (800 PSI 2-1/2"-3")
- CF8M Body, 316 Stainless Steel Ball and Stem
- RTFE Seats
- Temperature -20°F to 450°F

NPT SIZE	PART #
1/4"	S3F-2W
3/8"	S3F-3W
1/2"	S3F-4W
3/4"	S3F-6W
1"	S3F-8W
1-1/4"	S3F-10W
1-1/2"	S3F-12W
2"	S3F-16W
2-1/2"	S3F-20W
3"	S3F-24W

