

# S3F22 SERIES 3-PIECE STAINLESS 2-WAY FIRE SAFE BALL VALVES



ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE



## VALVE: Specifications

- 2-Way Stainless Steel Full Port
- 29Hg-2250 PSI W.O.G. Cold Non-Shock, 250 PSI WSP
- Body + Ball CF8M Stainless Steel, Live Loaded Stem 17-4PH Stainless Steel
- Seats, TFM standard, *See Chart Below*
- Fire Safe to API607-4, (w/suffix "G", G=graphite stem packing)
- Temperature Determined by Seat Material, *See Chart Below*
- ASME/ANSI B16-34 Class 600
- Meets NACE MRO175
- Federal Specification WW-V-35C Type
- All Valves Tested to API-598

VALVE SIZE	THREADED PART #	SOCKET WELD PART #	BUTT WELD PART #
1/4"	S3F22-2	S3F22-2W	S3F22-2B
3/8"	S3F22-3	S3F22-3W	S3F22-3B
1/2"	S3F22-4	S3F22-4W	S3F22-4B
3/4"	S3F22-6	S3F22-6W	S3F22-6B
1"	S3F22-8	S3F22-8W	S3F22-8B
1-1/4"	S3F22-10	S3F22-10W	S3F22-10B
1-1/2"	S3F22-12	S3F22-12W	S3F22-12B
2"	S3F22-16	S3F22-16W	S3F22-16B

Pressure/Temperature Specifications

