

CWFF150 SERIES CARBON ANSI 150 WAFER FLANGED VALVES

ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE



CWFF150 SERIES

- Full Port
- 29"hg - 285 PSI, Cold Non-Shock
- Carbon Steel A105 ANSI 150
- Stainless Steel Ball and Stem
- Temperature -4°F to 366°F
- P.T.F.E. Seats, Packing & Thrust Washer
- Blow Out Proof Stem, Adjustable Stem Packing

SIZE	PART #
1/2"	CWFF150-4
3/4"	CWFF150-6
1"	CWFF150-8
1-1/4"	CWFF150-10
1-1/2"	CWFF150-12
2"	CWFF150-16
2-1/2"	CWFF150-20
3"	CWFF150-24
4"	CWFF150-32
5"	CWFF150-40
6"	CWFF150-48
8"	CWFF150-64



CWFF300 SERIES CARBON ANSI 300 WAFER FLANGED VALVES

CWFF300 SERIES

- Full Port
- 29"hg - 740 PSI, Cold Non-Shock
- Carbon Steel A105 ANSI 300
- Stainless Steel Ball and Stem
- Temperature -4°F to 366°F
- P.T.F.E. Seats, Packing & Thrust Washer
- Blow Out Proof Stem, Adjustable Stem Packing

SIZE	PART #
1/2"	CWFF300-4
3/4"	CWFF300-6
1"	CWFF300-8
1-1/4"	CWFF300-10
1-1/2"	CWFF300-12
2"	CWFF300-16
2-1/2"	CWFF300-20
3"	CWFF300-24
4"	CWFF300-32
6"	CWFF300-48



C2FF150 SERIES CARBON FULL PORT ANSI 150 FLANGED VALVES

C2FF150 SERIES

- Full Port
- 29"hg - 285 PSI, Cold Non-Shock
- Carbon Steel A216 WCB, ANSI 150
- Live Loaded Stem Design, Anti-Static Device
- Standard Locking Device
- P.T.F.E. Seats, Packing & Thrust Washer
- Blow Out Proof Stem, Adjustable Stem Packing
- Temperature -50°F to 400°F
- Fire Safe Approved API 607-4 (w/suffix "G", G=graphite stem packing)

SIZE	PART #
1/2"	C2FF150-4
3/4"	C2FF150-6
1"	C2FF150-8
1-1/2"	C2FF150-12
2"	C2FF150-16
3"	C2FF150-24
4"	C2FF150-32
6"	C2FF150-48
8"	C2FF150-64

