

HYDRAULIC IN-LINE T-TYPE FILTERS

ALL SPECIFICATIONS AND DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE



HIT

HIT SERIES

- T-Type Filter
- Aluminum Housing
- 25 Micron Sintered Bronze Element
- 3,000 PSIG (Hydraulic only) Max. Working Pressure
- Buna "N" Seals -40°F to 200°F
- OPTIONS: Viton Seals, Suffix "V" -40°F to 400°F
Micron Size, Suffiz "10", "40", "90"
(Example HIT-290),(Kit Example EK2-90)

NPT SIZE	PART#	Element Kits	Spring Kits
1/4"	HIT-2	EK2	SK2T
1/4"	HIT-2V	EK2V	SK2T
3/8"	HIT-3	EK2	SK2T
3/8"	HIT-3V	EK2V	SK2T

SAE SIZE	PART#	Element Kits	Spring Kits
9/16"-18	HIT-S6	EK2	SK2T
9/16"-18	HIT-S6V	EK2V	SK2T

HYDRAULIC IN-LINE FILTERS



HIF

HIF SERIES

- Aluminum Housing
- 25 Micron Sintered Bronze Element
- 3,000 PSIG (Hydraulic only) Max. Working Pressure
- Buna "N" Seals -40°F to 200°F
- OPTIONS: Viton Seals, Suffix "V" -40°F to 400°F
Micron Size, Suffiz "10", "40", "90"
(Example HIF-290),(Kit Example EK2-90)

NPT SIZE	PART#	Element Kits	Spring Kits
1/4"	HIF-2	EK2	SK2
1/4"	HIF-2V	EK2V	SK2
3/8"	HIF-3	EK2	SK2
3/8"	HIF-3V	EK2V	SK2
1/2"	HIF-4	EK4	SK4
1/2"	HIF-4V	EK4V	SK4
3/4"	HIF-6	EK4	SK4
3/4"	HIF-6V	EK4V	SK4

SAE SIZE	PART#	Element Kits	Spring Kits
9/16"-18	HIF-S6	EK2	SK2
9/16"-18	HIF-S6V	EK2V	SK2
3/4"-16	HIF-S8	EK2	SK2
3/4"-16	HIF-S8V	EK2V	SK2

PNEUMATIC IN-LINE FILTERS



PIF

PIFB

PIF and PIFB SERIES

- (PIF) Aluminum Housing, (PIFB) Brass
- 40 Micron Sintered Bronze Element
- 500 PSIG Maximum Working Pressure
- Buna "N" Seals -40°F to 200°F
- M=Female Inlet/Male Outlet
- Female Inlet/Female Outlet: PIF-4 & PIF-6
- OPTIONS: Viton Seals, Suffix "V" -40°F to 400°F
Micron Size, Suffiz "20", "90"
(Example PIF-1M90),(Kit Example EK2-90)

NPT SIZE	PART#	Element Kits	Spring Kits
1/8"	PIFB-1M	EKP2	SKP2
1/8"	PIF-1M	EKP2	SKP2
1/4"	PIF-2M	EKP2	SKP2
3/8"	PIF-3M	EKP2	SKP2
1/2"	PIF-4	EKP4	SKP4
1/2"	PIF-4M	EKP4	SKP4
3/4"	PIF-6	EKP4	SKP4
3/4"	PIF-6M	EKP4	SKP4

