


ACTUATOR NOTES	
HOUSING MATERIAL	HIGH IMPACT PLASTIC
RATINGS/CERTIFICATIONS	IP67
OPERATING TEMP	-4°F TO 131°F
TORQUE	266 IN/LBS (30 Nm)
0° TO 90° CYCLE TIME	8 SEC.
VOLTAGES AVAILABLE:	12 VAC/DC 1.2 AMP
	24VAC/DC 0.6 AMP
	100-240 VAC 0.4-0.2 AMP
LIMIT SWITCHES	2 INTERNAL, STANDARD
INTERNAL HEATER	STANDARD FEATURE
BATTERY BACKUP FAILSAFE	OPTIONAL
4-20mA FEEDBACK	OPTIONAL



DRAWING NAME:  
30 SERIES ELECTRIC ACTUATOR:  
(12VAC/DC, 24 VAC/DC, 110-240 VAC)

MATERIAL:	<b>A</b>	DRAWING NUMBER: VB030-0XX	REV. <b>2</b>
SCALE: N.T.S.	NAME: MCH	DATE: 10-24-18	

THIS DOCUMENT IS PROPERTY OF UNIVERSAL COMPONENTS, INC.  
ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS DOCUMENT IS  
EXPRESSLY PROHIBITED UNLESS OTHERWISE AGREED UPON IN WRITING.  
\*ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.\*